



FIELD DOCUMENTATION

Measure the opening. *The factory does the rest.*

One sheet per opening. Complete every applicable section before placing the order. The factory adds tolerances — record the raw opening only.

PROJECT INFORMATION

PROJECT / JOB

DATE

CUSTOMER

OPENING ID

INSTALLER

PHONE / EMAIL

MOUNT TYPE — SELECT ONE

- ☐ **Inside mount** — system mounts within the existing opening. Default.
- ☐ **3-sided face mount** — mounts to the face of the surrounding wall. Sill adheres directly to the floor.
- ☐ **4-sided face mount** — used when no floor exists for the sill: window openings, door openings without a threshold.

Inside-mount minimum depths. Jamb: 1- $\frac{5}{8}$ " (41 mm) · Top track: 1- $\frac{13}{16}$ " (46 mm). If the opening does not meet both, face-mount on a flat surface around the opening.

SPAN CONFIGURATION — SELECT ONE

- ☐ **Single** — one cartridge, openings up to 144" wide.
- ☐ **Dual Lateral (DL)** — two cartridges joined at the factory. Pulls from one side.
- ☐ **Dual Central (DC)** — two cartridges, one on each jamb. Pull bars meet and close magnetically at center.

Single span maximum **144" wide**. Openings over 144" must use DL or DC. Maximums: single 144" × 120", dual 288" × 120" (W × H).



OPENING MEASUREMENTS

Measure the raw opening corner-to-corner. The factory adds the ½" cartridge oversize for magnetic closure — **do not add it to your numbers.** If width or height varies by more than ¼" across the three measurements, contact Element 13 before ordering.

WIDTH – THREE POINTS	INCHES	NOTES
Width at top		
Width at middle		
Width at bottom		

HEIGHT – THREE POINTS	INCHES	NOTES
Height at left jamb		
Height at middle		
Height at right jamb		

STACK SIDE & CLEARANCE

When retracted, the pleat stack sits against the base jamb. Stack width grows with screen width — confirm clear space on the chosen side.

☐ Base jamb: left
☐ Base jamb: right
☐ DC — stack sits on both jambs, pull bars meet at center
☐ Clear space on the base-jamb side meets or exceeds the stack width, plus handle and hardware clearance
☐ Nothing in the stack zone obstructs the cartridge — door hardware, sidelite mullions, drapery

STACK-WIDTH REFERENCE

SCREEN WIDTH	ST STACK	XL STACK
Up to 4'	4 - ¾"	—
5'	4 - ¾"	—
6'	4 - ¾"	—
7'	5 - ¾"	5 - ¾"
8'	5 - ¾"	6"
9'	5 - ¾"	—
10'	—	7"
12'	—	8"
14'	—	9"
16'	—	10"

SCREENS OVER 9' TALL (PE MESH) ADD ½" · FACE MOUNT ADDS 10 MM (¾") TO ALL STACK WIDTHS